

Single unit = 2 cars  
Double unit = 4 cars

Suitable for condominium and office buildings.  
For permanent use only!


Both platforms are inclined.

**Load per platform max. 2000 kg**  
(load per wheel max. 500 kg)


**X** = only applicable if garage doors are to be fitted.  
For roller doors x = 10 / 15 cm

**X** = to be clarified with door supplier

Dimensions in cm




### ■ PARKLIFT 340-155/150 (height 305)



|           | car height                       | distance (h) |
|-----------|----------------------------------|--------------|
| <b>UL</b> | only cars up to 160 cm           | 158          |
| <b>LL</b> | cars/station wagons up to 154 cm |              |

UL = upper level, LL = lower level



### ■ PARKLIFT 340-155/150 (height 295)



|           | car height                       | distance (h) |
|-----------|----------------------------------|--------------|
| <b>UL</b> | only cars up to 150 cm           | 158          |
| <b>LL</b> | cars/station wagons up to 154 cm |              |

Please attend to restricted car- and platform distance height! If higher cars or platform distance heights are requested, we suggest to use our PARKLIFT 450 system.

### ■ Clearance profile (car/station wagon)



\*The total car height includes roof rail and antenna fixture and must not exceed the mentioned max. height dimension.

### ■ Notes

- Clear platform width of 250 cm for car widths of 190 cm (see width dimensions stated on page 2). For large touring sedans we recommend a clear platform width of at least 260–270 cm for single and 500 cm for double systems.
- For standard lowered cars or cars with front spoilers exceeding the above clearance profiles, we recommend to use our system *PARKLIFT 450*.
- Due to recent increases in car length dimensions, and potential future developments, a pit length of 540 cm is advisable. This offers bigger safety distances also for future cars.
- At the edge of the pit a 10cm wide, yellow-black marking according to ISO 3864 has to be provided by the purchaser (see "statics and construction requirements" on page 3).
- It is not possible to have channels or undercuts and/or concrete haunches along the pit floor-to-wall joints. In the event that channels or undercuts are necessary, the system width needs to be reduced or the pit needs to be wider.
- The manufacturer reserves the right to construction or model modifications and/or alterations. Furthermore, the right to any subsequent part modification and/or variations and amendments in procedures and standards due to technical and engineering progresses in the art or due to environmental regulation changes, are also hereby reserved.

## Width dimensions · Underground garages

All dimensions shown are minimum. Construction tolerances must be taken into consideration.  
All dimensions in cm.

The access to the PARKLIFT should be level for a distance of 300cm immediately in front of the pit (max.slope allowable 1%).  
Beyond this max. slope 10%.


### Wall to wall

Single unit (2 cars)




| Space required B | gives clear platform width |
|------------------|----------------------------|
| 260              | 230                        |
| 270              | 240                        |
| <b>280</b>       | <b>250</b>                 |
| <b>290</b>       | <b>260</b>                 |
| <b>300</b>       | <b>270</b>                 |

Double unit (4 cars)



| Space required B | gives clear platform width |
|------------------|----------------------------|
| 490              | 460                        |
| 510              | 480                        |
| <b>530</b>       | <b>500</b>                 |

Combinated unit (6 cars)



| Space required B | gives clear platform width |
|------------------|----------------------------|
| 750              | 460+230                    |
| 780              | 480+240                    |
| <b>810</b>       | <b>500+250</b>             |
| <b>820</b>       | <b>500+260</b>             |
| <b>830</b>       | <b>500+270</b>             |


Wall openings required between partitions for electrical and hydraulic conduits must be provided where applicable. Wall openings may not be closed after installation.

The driving aisle width to be compliant with country regulations locally in force.

Other width combinations as well as smaller widths are possible.


### Pillars outside pit

Single unit (2 cars)




| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 250                          | 240              | 230                        |
| 260                          | 250              | 240                        |
| <b>270</b>                   | <b>260</b>       | <b>250</b>                 |
| <b>280</b>                   | <b>270</b>       | <b>260</b>                 |
| <b>290</b>                   | <b>280</b>       | <b>270</b>                 |

Double unit (4 cars)



| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 480                          | 470              | 460                        |
| 500                          | 490              | 480                        |
| <b>520</b>                   | <b>510</b>       | <b>500</b>                 |

Combinated unit (6 cars)




| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 740                          | 730              | 460+230                    |
| 770                          | 760              | 480+240                    |
| <b>800</b>                   | <b>790</b>       | <b>500+250</b>             |
| <b>810</b>                   | <b>800</b>       | <b>500+260</b>             |
| <b>820</b>                   | <b>810</b>       | <b>500+270</b>             |

The driving aisle width to be compliant with country regulations locally in force.

Other width combinations as well as smaller widths are possible.


### Pillars inside pit

Single unit (2 cars)




| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 255                          | 245              | 230                        |
| 265                          | 255              | 240                        |
| <b>275</b>                   | <b>265</b>       | <b>250</b>                 |
| <b>285</b>                   | <b>275</b>       | <b>260</b>                 |
| <b>295</b>                   | <b>285</b>       | <b>270</b>                 |

Double unit (4 cars)



| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 485                          | 475              | 460                        |
| 505                          | 495              | 480                        |
| <b>525</b>                   | <b>515</b>       | <b>500</b>                 |

Combinated unit (6 cars)



| Space required wall-pillar B | pillar-pillar B1 | gives clear platform width |
|------------------------------|------------------|----------------------------|
| 745                          | 735              | 460+230                    |
| 775                          | 765              | 480+240                    |
| <b>805</b>                   | <b>795</b>       | <b>500+250</b>             |
| <b>815</b>                   | <b>805</b>       | <b>500+260</b>             |
| <b>825</b>                   | <b>815</b>       | <b>500+270</b>             |

The driving aisle width to be compliant with country regulations locally in force.

Other width combinations as well as smaller widths are possible.

### Important notes

If maximum platform widths are not installed, difficulties might arise when entering or exiting the cars on the parking units. This depends on the car type, the access and the individual driving behaviour.


For parking slots at edges or between walls, we recommend going for our maximum platform widths.  
For cars wider than 190 cm, platform width of 270/500 cm is required to enter and exit the car at drivers-side.

## Width dimensions · Garages with doors

All dimensions shown are minimum. Construction tolerances must be taken into consideration.  
All dimensions in cm.


The access to the PARKLIFT should be level for a distance of 300cm immediately in front of the pit (max.slope allowable 1%).  
Beyond this max. slope 10%.

### Single garages (2 cars)



| Space required B | B1         | gives clear platform width |
|------------------|------------|----------------------------|
| 260              | 230        | 230                        |
| 270              | 240        | 240                        |
| <b>280</b>       | <b>250</b> | <b>250</b>                 |
| <b>290</b>       | <b>260</b> | <b>260</b>                 |
| <b>300</b>       | <b>270</b> | <b>270</b>                 |

### Double garages (4 cars)




| Space required B | B1         | gives clear platform width |
|------------------|------------|----------------------------|
| 490              | 460        | 460                        |
| 510              | 480        | 480                        |
| <b>530</b>       | <b>500</b> | <b>500</b>                 |

x = for doors. See page 1

Wall openings required between partitions for electrical and hydraulic conduits must be provided where applicable. Wall openings may not be closed after installation.


The driving aisle width to be compliant with country regulations locally in force.

### Serial garages with single doors (2 cars)



| Space required B | B1         | gives clear platform width |
|------------------|------------|----------------------------|
| 260              | 230        | 230                        |
| 270              | 240        | 240                        |
| <b>280</b>       | <b>250</b> | <b>250</b>                 |
| <b>290</b>       | <b>260</b> | <b>260</b>                 |
| <b>300</b>       | <b>270</b> | <b>270</b>                 |

### Serial garages with double doors (4 cars)




| Space required B | B1         | gives clear platform width |
|------------------|------------|----------------------------|
| 490              | 460        | 460                        |
| 510              | 480        | 480                        |
| <b>530</b>       | <b>500</b> | <b>500</b>                 |

The driving aisle width to be compliant with country regulations locally in force.

## Statics and construction requirements


### Single unit



↑ Marking according to ISO 3864


- P1 = +36kN \*
- P2 = + 5kN
- P3 = -12kN
- P4 = +16kN
- P5 = ± 2kN
- P6 = +21kN
- P7 = - 8kN
- P8 = ±5kN

### Double unit



- P1 = +70kN
- P2 = + 6kN
- P3 = -17kN
- P4 = +27kN
- P5 = ±2kN
- P6 = +35kN
- P7 = -13kN
- P8 = ±8kN

\*all static loadings include the weight of the car



Bearing loads are transmitted to the pit floor by base plates of approximately 140 cm<sup>2</sup>, fixed by heavy duty anchor bolts to a depth of approximately 10-12cm. Base plate thickness min. 18 cm Concrete quality according to the static requirements of the building, but for the dowel fastening we require a concrete quality of min. C20/25. When fixing to waterproof concrete floors chemical anchors are employed (to be advised by WÖHR).

The front wall of the pits must be formed of concrete and must be perfectly flat and vertical without any protrusions.

The specified lengths to the support points are mean values. Please contact us for exact positions for any variations on the standard units.

## Electrical datas

| Item | Performance                     | Quantity            | Designation   | Position  | Frequency        |
|------|---------------------------------|---------------------|---|---|------------------|
| 1    | by customer                     | 1 unit              | electric meter  | in the feed cable                                   |                  |
| 2    | by customer                     | 1 unit              | fuse or automatic circuit breaker 3x16A slow blow acc. to DIN VDE 0100 p. 430 | in the feed cable                                   | 1 per power pack |
| 3    | by customer as locally required | as locally required | acc. to local power supply regulations 3Ph+N+PE* 230/400 V, 50 Hz             | feed cable to main switch                           | 1 per power pack |
| 4    | by customer                     | each 10 m           | equipotential bonding safety lead-out connection                              | corner pit floor/ rear wall                         |                  |
| 5    | by customer                     | 1 unit              | equipotential bonding safety compliant to the DIN EN 60204 standard           | from the lead-out connection to the PARKLIFT system | 1 per PARKLIFT   |

Items 6 – 14 are included in WÖHR's scope of delivery unless otherwise specified in the offer/order.

\* DIN VDE 0100 part 410 + 430 (not under permanent load) 3PH+N+PE (three-phase current) Note: Where a door is used to close the garage, the manufacturer of the door must be consulted before the electric cable is laid.

The power supply cabling for the main switch must be provided onsite for the date set for the start of the assembly procedures at the very latest. Lay-in and hook-up to the lockable main switch must strictly be performed onsite during the assembly procedures. Our assembly technicians working onsite can also be available to work together with the Electricians in order to verify the system's functional capabilities.

Should a verification of the system's functional capabilities be requested at a later date, said verification can be performed by WÖHR against compensation.

In compliance with the DIN EN 60204 standard provisions, all systems must be connected directly on site with an earthed equipotential bonding. The lead-out connection must be at a 10 m distance!

## Noise protection

Basis is the German DIN 4109 "Noise protection in buildings".

With the following conditions required 30 dB (A) in rooms can be provided:

- noise protection package from our accessory
- insulation figure of the construction of min.  $R'_w = 57$  dB
- walls which are bordering the parking systems must be done as single wall and deflection resistant with min.  $m^2 = 300$  kg/m<sup>2</sup>

– solid ceiling above the parking systems with min.  $m^2 = 400$  kg/m<sup>2</sup>

At differing constructional conditions additional sound absorbing measures are to be provided by the customer.

The best results are reached by separated sole plates from the construction.

### Increased noise protection:

If increased noise protection must be provided planning has to be confirmed on a project basis by WÖHR.

## Temperature

The installation is designed to operate between +5°C and +40°C. Atmospheric Humidity: 50% at +40°C. If the local circumstances differ from the above please contact WÖHR.

## Drainage

We recommend the provision of a drainage channel at the front of the pit which can either incorporate a pump sump 50 x 50 x 20 cm, or a connection into the storm water sewerage system via a petrol/oil interceptor. If the pump sump is not

accessible for manual drainage, the client must provide a pump on site to empty the pump sump. To prevent any possibility of contamination of the groundwater we recommend that the pit floor is coated with an oil proof paint.

## Conformity inspection (TÜV)

The parking systems comply with the EC Machinery Directive and with the DIN EN 14010. An additional, freely optional conformity inspection is furthermore performed by the TÜV SÜD.


## Illumination

Illumination has to be considered acc. to local requirements by client.


## Free spaces

Special drawings for free spaces to accommodate air ducts or other pipes can be requested at WÖHR Agent!

## Installation diagram



## Recesses and conduits for rotary switches with rolling and sectional gates



## Railings

The units need to be provided acc. EN ISO 13857 with safety railings if the gap between unit and wall exceeds 20cm. If walkways are arranged directly to the side or behind the systems, railings have to be provided by client acc. to local requirements, height min. 200 cm – this is applicable during the construction phase too.

## Maintenance

WÖHR and its foreign partners have an assembly and customer network. Annual maintenance is performed at conclusion of a maintenance contract.

## Protection against corrosion

Independent of a maintenance workings has to be carried out acc. to WÖHR Cleaning and Maintenance Instruction regularly.

Clean up galvanized parts and platforms of dirt and road salt as well as other pollution (corrosion danger)!

Pit must be always ventilated and deaired well.

## Parking place width

We recommend a clear platform width of at least 250 cm and/or of at least 500 cm for double systems.

## Dimensions

All dimensions shown are minimum. Construction tolerances must be taken into consideration. All dimensions in cm.

## Fire safety

Each and every fire safety requirement and all possible mandatory item(s) and equipment(s) (fire extinguishing systems and fire alarm systems, etc.) are to be provided by the customer.

## Notes

In case of standard lowered cars with spoilers, contact Company WÖHR or local agent.